

# THE BADGER


THE NEW ARTICULATED BOOM LIFT FOR **RAIL APPLICATIONS**  
DEVELOPED BY & MANUFACTURED EXCLUSIVELY FOR OZ EQUIPMENT RENTALS



# THE BADGER

## MEASUREMENTS

Weight**	8,500kg	18740lbs
Working height maximum	16.07m	52ft 2in
Platform height maximum	14.07m	46ft 2in
Horizontal reach maximum	7.65m	25ft 1in
Horizontal reach to side	5.2m	17ft 1in
Up and over clearance maximum	7.16m	23ft 6in
A. Platform length	0.76m	2ft 6in
B. Platform width	1.83m	6ft
C. Height - stowed	2.11m	6ft 11in
D. Length - stowed	6.83m	22ft 5in
E. Width	2.29m	7ft 6in
F. Wheelbase	2.03m	6ft 8in
G. Ground clearance - center	0.39m	1ft 3.5in



## PRODUCTIVITY

Lift Capacity	227kg	500lbs
Platform rotation	160°	
Vertical Jib rotation	135°	
Turntable rotation	50° from Centre Line	
Turntable tailswing	zero	
Drive speed - stowed		
- No Rail Engaged	8km/h	5mph
- Rail Engaged	12km/h	7.5mph
Drive speed - raised	1km/h	0.61mph
Gradeability		
- 4WD - stowed*	45%	
- Rail Engaged - stowed*	25%	
Turning radius - inside	1.70m	5ft 6in
Turning radius - outside	4.50m	14ft 9in
Controls	12 V DC proportional	
Tyres - RT Lug - Foam Filled	355/55 D625	

## POWER

Power source	Deutz diesel D2011L03i 3 cylinder diesel 35.8kW (48hp)
Auxiliary power unit	12 V DC
Hydraulic tank capacity	90.8L 24gal
Fuel tank capacity	64.4L 17gal


## STANDARDS COMPLIANCE

ANSI A92.5, CSA B354.4, EN 280, AS 1418.10

\* Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.

\*\* Weight will vary depending on options and/or country standards.

## RANGE OF MOTION



# PHONE 1800 234 235

21 EAST DERRIMUT CRESCENT, DERRIMUT VICTORIA 3030 AUSTRALIA

EMAIL [SHANE@OZEQUIPMENT.COM](mailto:SHANE@OZEQUIPMENT.COM)